

Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600133

· Trade name: PU Quick foam (MDI) E-COLL

· Article number: 4317784150835, 4317784150859

· UFI: 1QUQ-YY5T-8807-5HMP

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Polyurethane-sealent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May bur	st if heated.
Skin Irrit. 2	H315	Causes skin irritation.	
Eye Irrit. 2	H319	Causes serious eye irritation.	
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties	es if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.	
Carc. 2	H351	Suspected of causing cancer.	
Lact.	H362	May cause harm to breast-fed children.	
STOT SE 3	H335	May cause respiratory irritation.	
STOT RE 2	H373	May cause damage to organs through prolonged or repeated Route of exposure: Oral.	exposure.
Aquatic Acute 1	H400	Very toxic to aquatic life.	
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.	
•			(Contd. on page 2

2)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS07 GHS08 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues alkanes, C14-17, chloro

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure. Route of exposure:

Orál

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dusts or mists.

P263 Avoid contact during pregnancy and while nursing.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. EUH204 Contains isocyanates. May produce an allergic reaction.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 2)

As from 24 August 2023 adequate training is required before industrial or professional use.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 9016-87-9 Reg.nr.: 01-2119457024-46-xxxx	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	25-50%		
CAS: 85535-85-9 EINECS: 287-477-0 Index number: 602-095-00-X Reg.nr.: 01-2119519269-33	alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Lact., H362	25-50%		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280	2.5-10%		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220 Acute Tox. 2, H330 Press. Gas (Comp.), H280	2.5-10%		
·SVHC				
CAS: 85535-85-9 alkanes, C14-17, chloro				

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Take affected persons out into the fresh air.

(Contd. on page 4)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 3)

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

· 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks Breathing difficulty Coughing

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

Foam

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Can form explosive gas-air mixtures.

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 4)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Suppress gases/fumes/haze with water spray.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Respiratory protection:

Short term filter device:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Hand protection



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 6)

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Different according to colouring

Odour: CharacteristicOdour threshold: Not determined.

• Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

• Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 4.200 hPa

Density and/or relative density

Density at 20 °C: 0.97 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

Change in condition

· Softening point/range

Oxidising propertiesEvaporation rateNot determined.Not applicable.

Information with regard to physical hazard classes

• Explosives Void • Flammable gases Void

· Aerosols

Extremely flammable aerosol. Pressurised container: May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids

Void
Void

(Contd. on page 8)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

		(Contd. of page 7)	
· Self-reactive substances and mixtures	Void		
· Pyrophoric liquids	Void		
· Pyrophoric solids	Void		
· Self-heating substances and mixtures	Void		
· Substances and mixtures, which emit flammable			
gases in contact with water	Void		
· Oxidising liquids	Void		
· Oxidising solids	Void		
· Organic peroxides	Void		
· Corrosive to metals	Void		
· Desensitised explosives	Void		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Danger of polymerisation.

Reacts with alcohols, amines, aqueous acids and alkalis.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues				
Oral	LD50	10,000 mg/kg (rat) (Literatur)		
Dermal	LD50	>5,000 mg/kg (rabbit) (Literatur)		
Inhalative	LC50/4h	11 mg/m³ (rat)		
CAS: 855	CAS: 85535-85-9 alkanes, C14-17, chloro			
Oral	LD50	>4,000 mg/kg (rat)		
Dermal	LD50	>13,500 mg/kg /(24h) (rabbit)		

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 8)

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity

May cause harm to breast-fed children.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. Route of exposure: Oral.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 75-28-5 isobutane

EC50 (48h) 69.43 mg/L (daphnia)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Toxic for aquatic organisms

(Contd. on page 10)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 9)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 05 01* waste isocyanates

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS AFROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2 Gases.

· Label 2.1

· 14.4 Packing group

· **ADR** Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

(Contd. on page 11)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 10)

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Directive 2012/18/EU
- · Seveso category

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 12)



Printing date 21.02.2022 Version number 305 (replaces version 304) Revision: 21.02.2022

Trade name: PU Quick foam (MDI) E-COLL

(Contd. of page 11)

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: Product safety department

· Contact: Head of Product Safety Department Date of previous version: 21.02.2022 · Version number of previous version: 304

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

Lact.: Reproductive toxicity - effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· * Data compared to the previous version altered.