




Zylinderschaft DIN 1897 R

Schneidstoff
Typ
Oberfläche
Bestell-Nr.

	HSS		HSS-Co5		HSS-Co5	
	N		VA		GU500DZ	
	Dampfbehandelt		Dampfbehandelt		TiN	
	42 11003		42 11004		42 11006	
						
	v_c m/min	VR-Code	v_c m/min	VR-Code	v_c m/min	VR-Code
	27	6	45	-	-	-
	22	5	35	-	-	-
	30	6	50	-	-	-
	30	5	40	5	6	6
	25	5	42	-	-	-
	25	5	35	5	6	6
	-	-	22	4	5	5
	-	-	18	4	5	5
	-	-	15	3	4	4
	30	6	40	-	-	-
	-	-	20	4	5	5
	-	-	15	3	4	4
	-	-	18	4	5	5
	-	-	12	3	4	4
	16	4	18	4	5	5
	-	-	13	3	4	4
	-	-	13	3	4	4
	-	-	-	2	3	3
	-	-	18	4	5	5
	-	-	12	3	4	4
	-	-	15	3	4	4
	-	-	-	-	2	2
	-	-	-	-	-	-
	-	-	-	1	2	2
	30	6	45	6	7	7
	30	6	36	6	7	7
	25	6	40	6	7	7
	20	6	28	6	7	7
	-	-	-	3	4	4
	-	-	-	2	3	3
	-	-	-	2	3	3
	70	-	70	-	-	-
	70	-	70	-	-	-
	50	7*	85	-	-	-
	50	6*	70	-	-	-
	70	6*	70	-	-	-
	60	5*	32	-	-	-
	70	-	63	-	-	-
	40	5*	40	-	-	-
	30	4*	50	4	6	6
	25	4*	35	4	5	5
	15	30	32	4	5	5
	-	-	28	4	5	5
	18	4	25	4	-	-
	28	5*	15	-	-	-
	-	-	-	-	-	-
	-	-	-	-	-	-

R rechtsschneidend

* Nur blanke Bohrer bzw. Bohrer mit blank ausgeschliffenen Nuten verwenden.